www.flotekafrica.com





FLO-TEK FLOWGUARD CPVC PLUMBING SOLUTION

The New and Innovative Plumbing Technology for Hot and Cold Water Applications



BUILDERS AND CONTRACTORS TRUST FLOWGUARD CPVC PIPING SYSTEMS **PERFORMANCE FOR OVER 50 YEARS.**

Flo-tek Flowguard CPVC Benefits

- ✓ Hot & Cold Water Application ✓ Advanced Insulating Properties
- Corrosion Resistance
- Easy Installation
- Cost Effective

- ✓ Sustainability High Chlorine Resistant
- Greater Material Safety Human Health



APPLICATIONS

The Flowquard CPVC Piping system has been installed worldwide for over 50 years in domestic and commercial projects. Our piping system comes standard in diameter sizes of 16mm – 110mm and are suitable for:

- Apartments / Town Houses
- Universities
- Hotels & Lodges
- Hospitals & Healthcare Facilities
- Retail stores
- Restaurants
- Schools
- Residential homes



ABOUT LUBRIZOL

Through product innovation, technical expertise and the many value-added services it offers customers, Lubrizol continues to advance CPVC solutions for the building and construction market.

From design of the base materials, to the production of resins and compounds, Lubrizol has established world-class research and development capabilities, differentiating it from its competitors and setting a higher standard for product quality.

Put the CPVC advantage to work for you. There is no better solution for your residential and commercial plumbing needs than a FlowGuard® Pipe & Fitting CPVC systems

©2015 The Lubrizol Corporation, all rights reserved. All marks are the property of the Lubrizol Cornoration

The Lubrizol Corporation is a Berkshire Hathawaycompany

www.lubrizolcpvc.com



FLO-TEK FLOWGUARD CPVC PIPING SYSTEM JOINTING PROCESS

Flo-tek Flowquard CPVC Piping system installation is AS EASY AS 1, 2 & 3... Just CUT, GLUE & JOIN!

TOOLS NEEDED

- **1. A Pipe Cutter**
- 2. A Chamfering Tool
- 3. CPVC Solvent Cement



CUT

- piping end.

GLUE

JOIN hold for 30 seconds.



Cut the pipe squarely using a wheel-type plastic tube cutter. Use a chamfering tool or file to remove burrs and filings from the inside and outside of the pipe.

Wipe any dirt or moisture from the fitting sockets and

 Apply a heavy, even coat of cement on the pipe end. Apply a thin coat inside the fitting socket.



 Immediately insert the pipe into the fitting socket. Rotate the pipe a guarter turn while inserting and





OUR PRODUCTS











OUR NETWORK

Angola Botswana Namibia South Africa Zambia South Africa Tel: +27 11 316 6891 Fax: +27 11 316 6896 Botswana Tel: +267 533 2180 Fax: +267 533 3146 **Angola** Tel: +244 2222 90662 Fax: +244 2222 90880 Namibia Tel: +264 61 244239 Fax: +264 61 232339

www.flotekafrica.com

Flo-Tek Botswana

Email: info@flotekafrica.com

otonamouloom